

## 1394C-SJT10-C

## Allen Bradley Panelview – Servo Controllers

| Technical Specifications:                |   |
|--|---|
| Manufacturer                             | Rockwell Automation                               |
| Brand                                    | Allen-Bradley                                     |
| Part Number/Catalog No.                  | 1394C-SJT10-C                                     |
| Product Line                             | Servo Controller                                  |
| Module Type                              | System  |
| Power Rating                             | 5 Kilowatt  |
| Input Phase                              | 3 Phase   |
| Series Enhancements                      | Terminations, Filtering (EMI), and Smart<br>Power |
| Factory-Installed Options                | GMC Turbo- IMC S Class                            |
| GMC Options                              | AxisLink and Remote I/O                           |
| Input Voltage                            | 360-480AC Volts                                   |
| Nominal Bus Output Voltage 380/460 Volts | 530/680 Volts DC                                  |
| Continuous Power Output 380/460 Volts    | 8/10 Kilowatts                                    |
| Peak Power Output                        | 28 Kilowatts                                      |
| Efficiency                               | 99%   |
| Continuous Current Output                | 14.73 Amperes                                     |
| Peak Current Output                      | 29.46 Amperes                                     |
| Line Loss Ride Through                   | 20 ms   |

(Table continued on next page)

DO Supply Inc. DOES NOT WARRANT THE COMPLETENESS, TIMELINESS OR ACCURACY OF ANY OF THE DATA CONTAINED on this PDF document. ALL INFORMATION CONVEYED HEREBY IS PROVIDED TO USERS "AS IS." IN NO EVENT SHALL DO Supply Inc. BE LIABLE FOR ANY DAMAGES OF ANY KIND INCLUDING DIRECT, INDIRECT, INCIDENTAL, CONSEQUENTIAL, LOSS PROFIT OR DAMAGE.

| Technical Specifications (Cont.): |
|-----------------------------------|
|-----------------------------------|

| 324-528 Volts AC, 50-60 Hertz, 3 Phase     | 324-528 Volts AC, 50-60 Hertz, 3 Phase     |
|--|--|
| 13.0 Amperes                               | 13.0 Amperes                               |
| 8 Amperes < 1 Microsecond                  | 8 Amperes < 1 Microsecond                  |
| 23.5 lbs (10.68 kg)                        | 23.5 lbs (10.68 kg)                        |
| 13.8 x 11.0 x 5.91 in (350 x 280 x 150 mm) | 13.8 x 11.0 x 5.91 in (350 x 280 x 150 mm) |

DO Supply Inc. DOES NOT WARRANT THE COMPLETENESS, TIMELINESS OR ACCURACY OF ANY OF THE DATA CONTAINED on this PDF document. ALL INFORMATION CONVEYED HEREBY IS PROVIDED TO USERS "AS IS." IN NO EVENT SHALL DO Supply Inc. BE LIABLE FOR ANY DAMAGES OF ANY KIND INCLUDING DIRECT, INDIRECT, INCIDENTAL, CONSEQUENTIAL, LOSS PROFIT OR DAMAGE.