



1783-US5T

Allen Bradley PLC – Stratix 2000

Technical Specifications:	
Manufacturer	Rockwell Automation
Brand	Allen-Bradley
Part Number/Catalog No.	1783-US5T
Total Ports	5
RJ45 Ports	5 Fast Ethernet
SFP Ports	0
Max Inrush Current	1.85 A
Power Input	24 V (12-48 V DC, 18-30 V AC, 50/60 Hz), SELV
Max Power Consumption	3.4 W
Nom Current	DC 180 mA; AC 360 mA
Max Current	DC 380 mA; AC 750 mA
Wire Size: Ground Connection	2.5 mm ² (14 AWG) Copper Wire Suitable for 187 degrees F (86 degrees C) Above Surrounding Ambient Temperature Outside the Enclosure, with Suitable Ring Terminal
Wire Size: DC Power Connection	4 x 0.25 mm ² (12 or 24 AWG) Twisted-Pair Copper Wire Suitable for 187 degrees F (86 degrees C) Above Surrounding Ambient Temperature Outside the Enclosure
Power Terminal Screw Torque	4.5x 5.0 in -lb (0.50 x 0.56 N - m)
Max Ground Terminal Screw Torque	8.05 in -lb
Enclosure Type Rating	Open-Style/None
Dimensions	4.51 x 3.02 x 1.17 in (114.5 x 76.8 x 29.6 mm)